

“UCN” MODELS

Water Level depth from bottom of cylinder*		Water Required for Fill to Indicated Depth All “UCN” Model Washer Extractors									
		UCN020		UCN030		UCN040		UCN060		UCN080	
inches	mm	gallons	liters	gallons	liters	gallons	liters	gallons	liters	gallons	liters
0	0	0.8	2.9	1.2	4.7	1.1	4.2	1.5	5.5	2.33	8.8
1	25	1.5	5.8	2.2	8.2	2.2	8.3	2.8	10.7	3.98	15.0
2	51	2.5	9.5	3.3	12.6	3.6	13.7	4.5	17.1	6.05	22.9
3	76	3.6	13.8	4.7	17.8	5.3	20.1	6.5	24.7	8.5	32.0
3.75	95	4.6	17.2	5.8	22.0	6.7	25.3	8.2	30.9	10.4	39.5
4	102	4.9	18.4	6.2	23.5	7.2	27.1	8.7	33.0	11.1	42.2
4.75	121	5.9	22.3	7.4	28.0	8.7	32.9	10.5	39.7	13.4	50.7
5	127	6.2	23.5	7.8	29.6	9.2	34.7	11.1	42.1	14.1	53.2
5.5	140	6.9	26.1	8.7	32.9	10.2	38.7	12.4	46.8	15.6	59.0
6	152	7.6	28.8	9.6	36.2	11.3	42.9	13.7	51.7	16.8	63.6
6.25	159	7.9	29.9	10.0	37.9	10.9	41.3	14.4	54.5	17.7	67.0
6.5	165	8.4	31.8	10.5	39.7	12.4	46.9	15.0	56.8	18.7	70.8
7	178	9.1	34.4	11.4	43.1	13.6	51.4	16.4	61.9	20.5	77.5
8	203	10.5	39.7	13.3	50.2	15.9	60.4	19.2	72.5	23.9	91
8.5	216	11.4	43.1	14.2	53.8	16.4	62	20.6	78.0	25.7	97
8.75	222	11.8	44.7	14.7	55.6	16.7	63.2	21.4	81.0	26.6	100.7
9	229	12.2	46.0	15.2	57.5	18.4	69.6	22.1	83.5	27.5	104
9.5	241	13.0	49.2	16.2	61.3	19.7	74.6	23.6	89.3	28.4	107.5
10	254	13.8	52.1	17.2	65.1	20.9	79.1	25.1	94.9	31.2	118
10.5	267	14.6	55.1	N/A	N/A	22.2	83.9	26.6	100.6	33.1	125
11	279	14.6	55.1	N/A	N/A	22.2	83.9	26.6	100.6	35.0	133
11.5	282	15.0	56.8	N/A	N/A	22.8	86.3	27.4	103.7	37.3	141.2
12	305	15.4	58.2	N/A	N/A	23.4	88.7	28.1	106.5	38.9	147
13	330	N/A	N/A	N/A	N/A	26.1	98.6	31.3	118.4	42.9	162
14	356	N/A	N/A	N/A	N/A	28.7	108.7	34.5	130.4	47.0	178
15	381	N/A	N/A	N/A	N/A	31.4	118.8	37.7	142.7	51.1	193

* Depth of water from bottom of cylinder (not the bottom of the shell). Allowance is made for filling the sump and shell up to the cylinder (0 inches). Water volumes are based on an empty washer (no load). The Technical manual requires that water levels be set with the washer empty.

- Saturation of dry load = 0.25 gallons per pound (2.0 liters per kilogram)
- Saturation of load after intermediate spin = 0.20 gallons per pound (1.7 liters per kilogram)

Soap dispenser valve water consumption for all models = 1.9 gallons per minute (7.2 liters per minute) minimum.

LEGEND	
	Low Level Fill
	Medium Level Fill
	High Level Fill